


Manufacturer	MaxStream, Inc.
Part Number	A09-F5NF
Photo	
Specific Freq. (MHz)	915
Gain	5.1dBi (3dBd)
Maximum Power Input (Watts)	100
Product Narrative	5.1 dBi gain base station. Heavy wall, gold anodized 1 1/4" aluminum mounting sleeve Precision copper clad elements sealed in white ultraviolet-inhibiting fiberglass radome.for weatherability.
Type	Fiberglass Omni-directional 900 MHz
General Freq. (MHz)	902-928
Bandwidth @ Rated VSWR (MHz)	26
VSWR	1.5:1
Impedance	50 ohms
H. Beamwidth	360 Deg.
Vert. Beamwidth	33 Deg.
Polarization	Vertical
Lightning Prot.	DC Ground
Size (HxWxD")	25"
Weight (lbs)	1.0
Rated Wind Velocity (MPH)	125
Wind Load, (sq ft)	Not Specified
Lateral Thrust @ RWV	Not Specified
Bending Moment @ RWV (ft lbs)	Not Specified
Connector (direct)	Recessed type "N" female connector.
Jumper Included	None
Connector Placement	Bottom
Mount Hdw. Incl.	2 Extruded Aluminum brackets
Incl. Hardware Fits	Up to 2-1/2" pipe
Warranty	1 Year
Qty/Uom	1 EACH
List (\$)	\$174.70